



**SPECIFICATIONS:**

ELECTRICAL: 120VAC/1PH/60Hz/1Amp  
(POWER SUPPLY INPUT)  
(POWER SUPPLY OUTPUT/TIMER INPUT  
12VDC / 2 Amps)

VALVE CONNECTIONS: 1.5" NPT (f)  
MAXIMUM PRESSURE: 200 PSI @ 70 DEG.F  
ACTUATION TIME: 3 SECONDS

CONTROL: SELECTABLE - AUTO/OFF/MANUAL  
AUTO - TIMED FLUSH, ADJUSTABLE DIGITAL  
INTERVAL(OFF) AND DURATION(ON)  
(SW POSITION MAINTAINED)  
MANUAL - MOMENTARY FLUSH OPERATION  
WITH SWITCH PRESS

ENCLOSURE: NEMA4X DERATED TO NEMA3R

VALVE BODY MATERIAL: NYLON  
VALVE BALL MATERIAL: STAINLESS STEEL

**PRODUCT SPECIFICATION**

**MILLER LEAMAN** INC

800 Orange Ave. Daytona Beach FL 32114

DRAWN	MPG	8/11/2022
CHECKED		
ENG APPR.		
MKT APPR.		
SHEET 1 of 1	Ref:	ML22069

TITLE:  
**Automatic Timer  
Flush Package  
ATF2-150**